

Chemola™ Desco 750 High Temperature Hydrocarbon Service

Chemola™ Desco 750 is formulated with 100% synthetic oils and contains solid lubricants for effective lubrication at temperatures to 900°F.

Recommended Uses

Chemola™ Desco 750 can be used in aliphatic hydrocarbons, asphalt, hot oil, lubricating oils and steam.

Typical Characteristics

Appearance	Black, smooth, tacky
NLGI	3
Penetration (ASTM D217)	225-255
Worked Penetration, 60x (ASTM D217)	225-255
Base Oil	Synthetic and natural ester
Base Oil Viscosity	500 cSt at 40°C
Base Oil Pour Point	-4°F (-16°C)
Thickener	Inorganic
Additives	Antioxidant package
Solids Content	Graphite
Specific Gravity	1.0
Density (lb/gal)	8.6
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>550°F (288°C)
Temperature Range	-20°F to 900°F (-29°C to 482°C)
Storage Stability	Pass
Resistance to Water (FTM 5415)	Pass
Resistance to Mineral Spirits (FTM 5415 mod)	Pass
Resistance to HCI(aq)	Pass

*FOR USE IN GATE, BALL AND PLUG VALVES.

DO NOT USE ON OXYGEN SERVICE.Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com





Chemola[™] **Desco 750** High Temperature Hydrocarbon Service

Packaging Information

Item Number	Unit Size	Quantity
082072BBX	"B" stick 3/8" x 1-1/2"	72 per box
082032CBX	"C" stick 7/16" x 2-1/8"	32 per box
082028DBX	"D" stick 1/2" x 2-1/4"	28 per box
082014GBX	"G" stick 5/8" x 3-1/2"	14 per box
082016JBX	"J" stick 1-3/8" x 8-1/2"	16 per box
082012KBX	"K" stick 1-1/2" x 10-1/2"	12 per box
0820010CR	14 oz cartridge	10 per carton
0820010QB	10 lb can	
0820020WMS	20 lb pail	
0820040WMS	40 lb pail	
0820120KG	120 lb keg	
0820400DR	400 lb drum	

*FOR USE IN GATE, BALL AND PLUG VALVES.

DO NOT USE ON OXYGEN SERVICE.Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com



