

Chemola™ Desco 800 Aromatic Hydrocarbon Service

Chemola™ Desco 800 is a high purity synthetic lubricant formulated for enhanced resistance to aromatic hydrocarbons and gasoline. Its blend of heavy bodied synthetic oils promotes superior metal adhesion and resistance to hydrocarbon blends that have a high percentage of aromatic compounds.

Recommended Uses

Chemola™ Desco 800 can be used in aromatics, butane, propane, unleaded gasoline and xylene.

Typical Characteristics

Appearance	Dark amber, smooth, tacky
NLGI	3
Penetration (ASTM D217)	220-250
Worked Penetration, 60x (ASTM D217)	220-250
Base Oil	Synthetic ester blend
Base Oil Viscosity	40,000 cSt at 40°C
Base Oil Pour Point	10°F (-12°C)
Thickener	Inorganic
Additives	Antioxidant package
Specific Gravity	1.0
Density (lb/gal)	8.6
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>550°F (288°C)
Temperature Range	-20°F to 400°F (-29°C to 204°C)
Storage Stability	Pass
Resistance to Water (FTM 5415)	Pass
Resistance to Synthetic Condensate (FTM 5415 mod)	Pass
Resistance to Mineral Spirits (FTM 5415 mod)	Pass
Resistance to 20% Hexane in Mineral Spirits (FTM 5415 mod)	Pass
Resistance to Diesel Fuel (FTM 5415 mod)	Pass

*FOR USE IN GATE, BALL AND PLUG VALVES.

DO NOT USE ON OXYGEN SERVICE.Special packaging sizing available upon request.







Chemola™ Desco 800Aromatic Hydrocarbon Service

Packaging Information

Item Number	Unit Size	Quantity
080572BBX	"B" stick 3/8" x 1-1/2"	72 per box
080532CBX	"C" stick 7/16" x 2-1/8"	32 per box
080528DBX	"D" stick 1/2" x 2-1/4"	28 per box
080514GBX	"G" stick 5/8" x 3-1/2"	14 per box
080516JBX	"J" stick 1-3/8" x 8-1/2"	16 per box
080512KBX	"K" stick 1-1/2" x 10-1/2"	12 per box
0805010CR	14 oz cartridge	10 per carton
0805010QB	10 lb can	
0805020BM	20 lb pail	
0805040BM	40 lb pail	
0805120KG	120 lb keg	
0805400DR	400 lb drum	

*FOR USE IN GATE, BALL AND PLUG VALVES.

DO NOT USE ON OXYGEN SERVICE.Special packaging sizing available upon request.





